	S-S1					SDS
SDS Core Cutting Machine						ILLING SOLUTIONS NER WITH A SOLUTION
Technical Specifications Itechnical Specifications Dimensions and Weight; Itechnical Specifications						
► Lenght;	2000mm	it;			_	_
► Width;	820mm					
 Height; 	1255mm					
► Weight;	385kg					
Saw Engine;	303Kg		1	N/	_	
► RPM;	1500rpm					
 Power; 	3kW				_	
Saw;	350 mm			Contraction of the local division of the loc		
Cooling syste						
Coolant;	;,,	Cutting oil, 60l		•	-	
 Pump pow 	er.	0,09kW				
 Flow rate; 	<i>ci,</i>	60I/min				
 Pumping F 	leiaht [,]	6m				
 Oil tank ca 		721		V		
				1		21
Cores and Core Hausings; ► Hausing P-WL is combined with the main frame. Then, H-WL, N-WL and B-WL Hausings are added according to the core used.						
► B-WL;	Ø36,5m	m - 100cm				
► N-WL;	Ø47,6m	m - 100cm	a contraction of the second seco			
► H-WL;	Ø63,5m	m - 100cm			4	
► P-WL;	Ø85mm	- 100cm				

Informations;

Core cutting machine is used to obtain two half cylinders from rock, concrete and core samples of various sizes.

► It is made of 5mm steel.

▶ Painted with electrostatic powder paint resistant to scratches.

► It can cut Max.90mm diameter, Max.100cm core.

► The cutting process can be done automatically and the forward (cutting speed) and return speeds can be adjusted by the user separately by means of a reducer motor. Forward and reverse distances are secured with the help of a switch.

The water pump can be work longtime. The cooling of the cutting blade is done with water sprayed from the water pump.

► It can circulate its own water with the water tank and water pump mounted on the core cutting machine. The water tank capacity is 72lt. (it is recommended to add boron to the water tank with water)

Cutter head does not oscillate.

Core cutting machine have 4 legs and the wheels attached to these legs, you can easily move it.

► The core cutting machine has 380V industrial type male plug, electrical connection 3-phase, neutral and ground.

There is a special cover to prevent particles from dispersing and splashing water. The cover has piston and you can

open easily There are sensors to prevent the machine from working when this cover is open for security purposes.